

73/05/050687

REC'D 28 FEB 2004

WIPO

PCT

PA 1174317

THE UNITED STATES OF AMERICA

TO ALL TO WHOM THESE PRESENTS SHALL COME:

UNITED STATES DEPARTMENT OF COMMERCE

United States Patent and Trademark Office

May 25, 2004

THIS IS TO CERTIFY THAT ANNEXED HERETO IS A TRUE COPY FROM THE RECORDS OF THE UNITED STATES PATENT AND TRADEMARK OFFICE OF THOSE PAPERS OF THE BELOW IDENTIFIED PATENT APPLICATION THAT MET THE REQUIREMENTS TO BE GRANTED A FILING DATE UNDER 35 USC 111.


APPLICATION NUMBER: 60/549,191 ✓

FILING DATE: March 02, 2004 ✓

PRIORITY DOCUMENT

SUBMITTED OR TRANSMITTED IN
COMPLIANCE WITH RULE 17.1(a) OR (b)

**By Authority of the
COMMISSIONER OF PATENTS AND TRADEMARKS**



M. K. Hawkins

M. K. HAWKINS

Certifying Officer

PATENT APPLICATION SERIAL NO. _____

U.S. DEPARTMENT OF COMMERCE
PATENT AND TRADEMARK OFFICE
FEE RECORD SHEET

03/05/2004 NBIZUNES 00000098 141270 60549191

01 FC:1005 160.00 DA

PTO-1556
(5/87)

*U.S. Government Printing Office: 2002 — 489-267/59033

030204


Please type a plus sign (+) inside this box → PTO/SB/16 (02-01)
Approved for use through 10/31/2002. OMB 0651-0032
Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE
Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.**PROVISIONAL APPLICATION FOR PATENT COVER SHEET**

This is a request for filing a PROVISIONAL APPLICATION FOR PATENT under 37 CFR 1.53 (c).

Express Mail Label No. EV 312 068 706 US

Date of Deposit: March 2, 2004

INVENTOR(S)					
Given Name (first and middle [if any])	Family Name or Surname	Residence (City and either State or Foreign Country)			
GEORGE	MARMAROPOULOS	YORKTOWN HEIGHTS, NEW YORK			
<input type="checkbox"/> Additional inventors are being named on the _____ separately numbered sheets attached hereto					
TITLE OF THE INVENTION (280 characters max)					
A TIME-DELAY SOFT SWITCH					
CORRESPONDENCE ADDRESS					
Direct all correspondence to:					
<input checked="" type="checkbox"/> Customer Number		24737		→ <div style="border: 1px solid black; padding: 5px; display: inline-block;">24737</div>	
OR Type Customer Number here					
<input type="checkbox"/> Firm or Individual Name	PHILIPS ELECTRONICS				
Address	345 SCARBOROUGH ROAD				
Address					
City	BRIARCLIFF MANOR	State	NEW YORK	ZIP	10510
Country	USA	Telephone	(914) 333-9608	Fax	(914) 333-9615
ENCLOSED APPLICATION PARTS (check all that apply)					
<input checked="" type="checkbox"/> Specification Number of Pages		17		<input type="checkbox"/> CD(s), Number <input type="text"/>	
<input type="checkbox"/> Drawing(s) Number of Sheets		4		<input type="checkbox"/> Other (specify) <input type="text"/>	
<input type="checkbox"/> Application Data Sheet. See 37 CFR 1.76					
METHOD OF PAYMENT OF FILING FEES FOR THIS PROVISIONAL APPLICATION FOR PATENT (check one)					
<input type="checkbox"/> Applicant claims small entity status. See 37 CFR 1.27.					
<input type="checkbox"/> A check or money order is enclosed to cover the filing fees					
<input checked="" type="checkbox"/> The Commissioner is hereby authorized to charge filing fees or credit any overpayment to Deposit Account Number: 14-1270					
<input type="checkbox"/> Payment by credit card. Form PTO-2038 is attached.					
FILING FEE AMOUNT (\$) 160.00					
The invention was made by an agency of the United States Government or under a contract with an agency of the United States Government.					
<input checked="" type="checkbox"/> No.					
<input type="checkbox"/> Yes, the name of the U.S. Government agency and the Government contract number are: _____					

Respectfully submitted,
SIGNATURE

Date March 2, 2004

TYPED or PRINTED NAME

Aaron Waxler

REGISTRATION NO.: 48,027
(if appropriate)

Docket Number: US040067

TELEPHONE

(914) 333-9608

USE ONLY FOR FILING A PROVISIONAL APPLICATION FOR PATENT

This collection of information is required by 37 CFR 1.51. The information is used by the public to file (and by the PTO to process) a provisional application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.14. This collection is estimated to take 8 hours to complete, including gathering, preparing, and submitting the complete provisional application to the PTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, Box 1450, Alexandria, VA 22313-1450. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Box Provisional Application, Assistant Commissioner for Patents, Box 1450, Alexandria, VA 22313-1450

A TIME-DELAY SOFT SWITCH

The present invention relates to time-delay switches. More particularly, the present invention relates to a time-delay soft switch using the elastomeric properties of two or more materials relative to each other.

5 In smart fabric applications, it is frequently desirable to control the operation of electrical devices, such as those associated with some wearable electronics, by means of switches which operate on a predetermined time-delay. Conventionally, switches of this sort utilize mechanical, thermal and/or electrical means to obtain the desired time-
10 delay interval. Other such devices use gravity operated mechanisms to realize a time-delay function. These conventional devices can be costly to manufacture, are normally structurally complex, comprise a substantial number of operative components including, for example, electrically-driven or spring-operated timing mechanisms, and have often proven to be
15 operatively impractical, especially in textile or smart fabric applications.

 Thus, it is useful to introduce a method and device that allows a time-delay for opening and/or closing an electric circuit, or the like, that is compatible with the soft, flexible characteristics of any of a variety of textiles or fabrics. It would be advantageous for such a device to be able
20 to be compatible with various textile languages and/or systems without adding components, thereby enabling permanent integration.

 It is an object of the present invention to provide a time-delay switch that operates using the elastomeric properties of two or more materials.

It is another object of the present invention to provide a time-delay switch for use any of a variety of pressure sensitive smart fabric applications.

It is another object of the present invention to provide a time-delay
5 switch that is capable of seamless integration into a wearable fabric application.

It is another object of the present invention to provide a time-delay switch that has at least two conductive surfaces that are selectively connected and/or disconnected via the elastomeric characteristics of at
10 least two different materials.

These and other objects and advantages of the present invention are achieved by a time-delay soft switch that has one or more first layers of material with first elastomeric properties. At least one of the one or more first layers has at least one first electrically conductive surface (12). The
15 time-delay soft switch also has one or more second layers of material with second elastomeric properties. The one or more second layers can be connected to one or more third layers of material and at least one of the one or more third layers can have a second electrically conductive surface. The one or more first layers preferably covering closely the one or more
20 second layers and the one or more third layers.

The present invention is more fully understood by reference to the

following detailed description of an illustrative embodiment in combination with the drawings identified below.

Fig. 1 is a schematic side section view of a time-delay soft switch in accordance with a first embodiment of the present invention, showing the
5 switch in a first state;

Fig. 2 is another schematic side section view of the time-delay soft switch of Fig. 1, showing the switch in a second state;

Fig. 3 is still another schematic side section view of the time-delay soft switch of Fig. 1, showing the switch in a third state;

10 Fig. 4 is yet another schematic side section view of the time-delay soft switch of Fig. 1, showing the switch returned to the first state;

Fig. 5 is a schematic side section view of a time-delay soft switch in accordance with a second illustrative embodiment of the present invention, showing the switch in a first state;

15 Fig. 6 is another schematic side section view of the time-delay soft switch of Fig. 5, showing the switch in a second state;

Fig. 7 is still another schematic side section view of the time-delay soft switch of Fig. 5, showing the switch in a third state; and

20 Fig. 8 is yet another schematic side section view of the time-delay soft switch of Fig. 5, showing the switch returned to the first state.

Referring to the drawings and in particular, Fig. 1, there is shown a time-delay soft switch in accordance with an illustrative embodiment of the present invention generally represented by reference numeral 1. The time-delay soft switch 1 has one or more first layers 10 of material having first
5 elastomeric properties and one or more second layers 20 of material having second elastomeric properties differing from those of one or more first layers 10. In addition, the time-delay soft switch 1 may have one or more third layers 30 of material having electrically conductive properties and suitable to be connected to one or more first layers 10 and/or one or
10 more second layers 20.

As shown, in a preferred aspect of the present invention, one or more first layers 10 may preferably have at least one first electrically conductive portion and/or surface 12. First conductive surface 12 may be inherently conductive via the properties or configuration of one or more first
15 layers 10. Alternatively, or in addition first conductive surface 12 may be made conductive using a conductive coating, for example, such as a conductive ink. First conductive surface 12 may be directly or indirectly connected to a power source and/or a separate electronic device (not shown).

20 Preferably, one or more first layers 10 of material may be made up of any of a variety of materials preferably having certain predefined elastomeric properties. For example, various polyurethane based

materials may be used. The degree of elasticity associated with one or more first layers 10 can preferably be adjusted or modified as desired during fabrication or manufacture.

In a one aspect of the present invention, one or more first layers 10
5 preferably have a relatively high or fast elastic recovery with respect to one or more second layers 20. However, in another aspect of the present invention, one or more first layers 10 may have a relatively low elastic recovery or response relative to one or more second layers 20.

One or more first layers 10 can have any of a variety of
10 constructions. For example, as shown, one or more first layers 10 can be a relatively shallow or flat foam, molded and/or formed using any of a variety of known conventional methods. Alternatively, one or more first layers 10 may be formed using fibers (not shown) having elastomeric properties. Also, one or more first layers 10 preferably have a sufficiently
15 high tensile strength, weight and consistency to provide a high degree of durable flexibility during manufacture and/or use (e.g., flexible, resilient, corrosion resistant, etc.). Further, one or more first layers 10 may be natural and/or synthetic, and preferably can be shaped, sized and/or configured, using conventional methods, into a multitude of different
20 patterns and/or forms to facilitate a variety of different applications in use, functional and/or aesthetic.

Regarding one or more second layers 20, as with first layers 10,

preferably one or more second layers 20 can be formed from any of a variety of materials preferably having certain predefined elastomeric properties. The elastomeric properties of one or more second layers 20 preferably differ from those of one or more first layers 10. The degree of
5 elasticity associated with one or more second layers 20 may, like first layers 10, be adjusted or modified as desired during fabrication or manufacture.

In a one aspect of the present invention, one or more second layers 20 preferably have a relatively low or slow elastic recovery with respect to
10 one or more first layers 10. However, in another aspect of the present invention, one or more second layers 20 may have a relatively high elastic recovery or response relative to one or more first layers 10.

One or more second layers 20 can have any of a variety of constructions. For example, as shown, second layers 20 may be a lofted
15 foam, molded and/or formed using various known conventional methods. Alternatively, as with first layers 10, one or more second layers 20 may be formed using fibers (not shown) with elastomeric properties or characteristics. Also, one or more second layers 20 can have a sufficiently high tensile strength, weight and consistency to provide a high degree of
20 durable flexibility during manufacture and/or use (e.g., flexible, resilient, corrosion resistant, etc.). Further, one or more second layers 20 may be natural and/or synthetic, and can be shaped, sized and/or configured,

using various conventional methods, into a multitude of different patterns and/or forms to facilitate a variety of different applications in use, functional and/or aesthetic.

In one aspect of the present invention, one or more second layers
5 20 can have at least one second electrically conductive portion and/or surface 22. Second conductive surface can be inherently conductive and/or made conductive using a conductive coating, for example, such as a conductive ink. The second conductive surface, like first conductive surface 12, can be directly or indirectly connected to a power source and/or
10 a separate electronic device.

As shown, in a preferred aspect of the present invention, one or more third layers 30 of preferably electrically conductive material overlay one or more second layers 20 to provide the second conductive surface 22. One or more third layers 30 may have at least some elastomeric
15 properties. Preferably, any elastomeric properties associated with one or more third layers 30 correspond proportionally to those of one or more second layers 20. The degree of conductivity and/or elasticity of one or more third layers 30 may, as with first layers 10 and second layers 20, be adjusted or modified as desired during fabrication or manufacture.

20 One or more third layers 30 can preferably have any of a variety of constructions. For example, third layers 30 can be a fiber mesh or web consisting of one or more electrically conductive fibers intertwined using

known conventional methods for weaving, sewing and/or knitting, for example. The conductive fibers and/or one or more third layers 30 may have appropriate elastomeric properties and/or a high tensile strength, a weight and a consistency sufficient to provide a high degree of durable
5 flexibility during manufacture and wear (e.g., flexible, resilient, corrosion resistant, etc.). One or more third layers 30 can have a variety of different shapes, sizes and/or configurations appropriate for various adaptations to accommodate different uses. One or more third layers 30 can have different conductivities and may be made of any suitable conductive
10 material, including for example, a metalized foil, a conductive polymer, or a graphitized or metalized material.

Having identified and discussed some of the various aspects of the present invention, in use, time-delay soft switch 1 may be easily implemented to any of a variety of circuit applications. For example, the
15 time-delay switch of the present invention may be seamlessly integrated as part of a pressure sensitive fabric application such as a wearable heart rate monitor, or as part of a pressure activated seat or seat cushion in such a manner so as to facilitate control and/or otherwise manipulate one or more electrical operations (e.g., power-on/power-off) associated with any of a
20 variety of electronic devices. Other and/or alternative applications are also within the scope of the present invention.

As shown in Fig. 1, in accordance with a first embodiment of the

present invention, one or more first layers 10 can be more elastically responsive relative to one or more second layers 20 and/or one or more third layers 30. In this embodiment, first layers 10 preferably cover one or more second layers 20 and/or one or more third layers 30 in a relatively
5 tight or close manner when in a relaxed state. Also as shown, first conductive surface 12 and second conductive surface 22 are preferably electrically connected and may cooperate to open/close at least one circuit preferably associated with one or more electronic devices.

Referring to Fig. 2, as shown, first and second conductive surfaces
10 12, 22 preferably remain in contact and/or electrically connected when switch 1 is compressed via a force F, for example. The duration for which switch 1 remains in this compressed state after force F is removed and/or switch 1 is released preferably depends at least substantially on the elastic recovery rate of one or more first layers 10, which, as previously stated,
15 may be adjusted during manufacture to satisfy any of a variety of timing requirements needed for a variety of applications in use.

Referring to Fig. 3, preferably one or more first layers 10 return to the relaxed state faster or sooner than one or more second layers 20 and/or one or more third layers 30 due at least substantially to the different
20 elastic recovery rates, or the relative elastomeric properties, associated with the various layers. Consequently, first conductive surface 12 and second conductive surface 22 may preferably be disconnected for a

predefined period of time or until one or more second layers 20 and/or one or more third layers 30 return to the relaxed state. The duration for which first and second conductive surfaces 12, 22 remain disconnected preferably depends on the elastic recovery rate of one or more first layers 10 with respect to those of one or more second layers 20 and/or one or more third layers 30.

Referring to Fig. 4, as shown, preferably once one or more second layers 20 and/or one or more third layers 30 return to the relaxed state, first and second conductive surfaces 12, 22 may be reconnected. It is noted that, as the elastomeric properties of the various layers 10, 20, 30 may be adjusted to be more or less elastically responsive relative to each other, the time period for which first and second conductive surfaces 12, 22 are connected and/or disconnected may likewise be adjusted as appropriate for an intended application in use.

Referring to Fig. 5, in accordance with a second embodiment of the present invention, one or more first layers 10 can be less elastically responsive to one or more second layers 20 and/or one or more third layers 30. In this embodiment, as shown, switch 1 preferably has essentially the same configuration as with the previous embodiment. However, in this embodiment, there is preferably a gap 40 separating one or more first layers 10 from one or more second layers 20 and/or one or more third layers 30 such that first conductive surface 12 and second

conductive surface 22 are preferably electrically disconnected when in the relaxed state. It is noted that first and second conductive surfaces 12, 22 of this embodiment may likewise cooperate to open/close at least one circuit preferably associated with one or more electronic devices.

5 Referring to Fig. 6, as shown, first and second conductive surfaces 12, 22 preferably remain in separated and/or electrically disconnected until switch 1 is compressed via a force F, for example. The duration for which switch 1 remains in this compressed state after force F is removed and/or switch 1 is released preferably depends at least substantially on the elastic
10 recovery rate of one or more first layers 10, which, as previously stated, may be adjusted during manufacture to satisfy any of a variety of timing requirements needed for a variety of applications in use.

 Referring to Fig. 7, preferably one or more first layers 10 return to the relaxed state slower than one or more second layers 20 and/or one or
15 more third layers 30 due at least substantially to the different elastic recovery rates, or the relative elastomeric properties, associated with the various layers. Consequently, first conductive surface 12 and second conductive surface 22 may preferably be connected for a predefined period of time or until one or more first layers 10 return to the relaxed state. The
20 duration for which first and second conductive surfaces 12, 22 remain connected preferably depends on the elastic recovery rate of one or more first layers 10 with respect to those of one or more second layers 20 and/or

one or more third layers 30.

Referring to Fig. 8, as shown, preferably once one or more first layers 10 return to the relaxed state, first and second conductive surfaces 12, 22 may be once again disconnected. It is noted that, as the
5 elastomeric properties of the various layers 10, 20, 30 may be adjusted to be more or less elastically responsive relative to each other, the time period for which first and second conductive surfaces 12, 22 are connected and/or disconnected may likewise be adjusted as appropriate for an intended application in use.

10 The present invention having been thus described with particular reference to the preferred aspects thereof, it will be obvious that various changes and modifications may be made therein without departing from the spirit of the present invention as defined herein.

WHAT IS CLAIMED IS:

1. A time-delay soft (1) switch comprising:

one or more first layers (10) of material having first elastomeric properties, said one or more first layers (10) having at least one first

5 electrically conductive surface (12); and

one or more second layers (20) of material having second elastomeric properties, said one or more second layers (20) having at least one second electrically conductive surface (22),

wherein said one or more first layers (10) closely cover said one or
10 more second layers (20).

2. The time-delay soft switch (1) of claim 1, wherein said at least one second electrically conductive surface (22) is one or more third layers (30) of conductive material connected to said one or more second layers (20).

15 3. The time-delay soft switch (1) of claim 1, wherein said first elastomeric properties of said one or more first layers (10) are more responsive relative to said second elastomeric properties of said one or more second layers (20).

20 4. The time-delay soft switch (1) of claim 2, wherein the soft switch is seamlessly integrated into a pressure sensitive smart fabric application.

5. The time-delay soft switch (1) of claim 2, wherein said first and second electrically conductive surfaces (22) are electrically connected when the soft switch is in a relaxed state.

6. The time-delay soft switch (1) of claim 2, wherein said first
5 and second electrically conductive surfaces (22) are electrically connected when the soft switch is in a compressed state.

7. The time-delay soft switch (1) of claim 3, wherein said first and second electrically conductive surfaces (22) electrically disconnect for a predefined period of time when the soft switch is compressed and
10 released.

8. The time-delay soft switch (1) of claim 7, wherein said first and second electrically conductive surfaces (22) electrically reconnect after said predefined period of time.

9. The time-delay soft switch (1) of claim 7, wherein said
15 predefined period of time is dependant on said first elastomeric properties of said one or more first layers (10) of material and said second elastomeric properties of said one or more second layers (20) of material.

10. The time-delay soft switch (1) of claim 3, wherein said one or more first layers (10) of material return to a relaxed state quicker than said
20 one or more second layers (20) of material when the soft switch is compressed and released.

11. The time-delay soft switch (1) of claim 1, wherein said first elastomeric properties of said one or more first layers (10) of material are less responsive relative to said second elastomeric properties of said one or more second layers (20) of material.

5 12. The time-delay soft switch (1) of claim 11, wherein said at least one second electrically conductive surface (22) is one or more third layers (30) of conductive material connected to said one or more second layers (20).

10 13. The time-delay soft switch (1) of claim 11, wherein the soft switch is used in pressures sensitive smart fabric applications.

14. The time-delay soft switch (1) of claim 11, wherein said first and second electrically conductive surfaces (22) are electrically disconnected when the soft switch is in a relaxed state.

15 15. The time-delay soft switch (1) of claim 11, wherein said first and second electrically conductive surfaces (22) are electrically connected when the soft switch is in a compressed state.

16. The time-delay soft switch (1) of claim 12, wherein said first and second electrically conductive surfaces (22) electrically connect for a predefined period of time when the soft switch is compressed and
20 released.

17. The time-delay soft switch (1) of claim 16, wherein said first and second electrically conductive surfaces (22) electrically re-disconnect after said predefined period of time.

18. The time-delay soft switch (1) of claim 16, wherein said
5 predefined period of time is dependant on said first elastomeric properties of said one or more first layers (10) of material and said second elastomeric properties of said one or more second layers (20) of material.

19. The time-delay soft switch (1) of claim 12, wherein said one or more second layers (20) of material return to a relaxed state faster than
10 said one or more first layers (10) of material when the soft switch is compressed and released.

20. The time-delay soft switch (1) of claim 1, wherein said one or more first layers (10) of material and said one or more second layers (20) of material operatively cooperate to selectively connect and/or disconnect
15 said first and second electrically conductive surfaces (22), and thereby close a circuit, for a predefined period of time via a pressure interaction.

ABSTRACT OF THE DISCLOSURE

There is provided a time-delay soft switch that has one or more first layers (10) of material with first elastomeric properties and one or more
5 second layers of material with second elastomeric properties differing from those of the one or more first layers (10). One or more first layers (10) and/or one or more second layers (20) are each provided with at least one electrically conductive portion surface (12, 22). The time-delay switch provides, via the relative elastomeric properties of the layers, a time delay
10 for opening and/or closing of an electric circuit that is compatible with the soft, flexible nature of a fabric.

1/4




FIG. 1




FIG. 2

2/4




FIG. 3




FIG. 4

3/4




FIG. 5




FIG. 6

4/4




FIG. 7




FIG. 8